

The AVR series is perfect as starter models for small to medium size marinas. With the low cost and high efficiency, these smaller units will service facilities up to 250 slips.



## AVR20

Low Cost Model for Small Marinas



## AVR60

Starter Model for Small Marinas



## AVR125

Suitable for Small and Medium Sized Marinas

Waubashene, Ontario  
CANADA

**Tel:** 705.538.1495

**Toll Free:** 800.663.1624  
(Canada & US Only)

**Fax:** 705.538.1776

**www.wmwpump.com**

STANDARD EQUIPMENT	AVR20	AVR60	AVR125
Motor	¼ Hp electric	¾ Hp electric	¾ Hp electric
Tank	25 US Gal. (94l)	65 US Gal. (246l)	115 US Gal. (435l)
Connections	1 ½" NPT Intake & discharge	2" NPT Intake & discharge w/ motorized ball valve	2" NPT Intake & discharge w/ motorized ball valve
Finish	Blue Metallic Top Hot Dipped Galv. Cycle Tank	White or Blue Metallic	White or Blue Metallic
Accessories (Incl.)	25 ft Intake Hose Assembly 2 Sizes Deck Adapters Universal Deck Adapter Potty Wand	33 ft. Intake Hose Assembly 2 Sizes Deck Adapters Universal Deck Adapter Potty Wand	33 ft Intake Hose Assembly 2 Sizes Deck Adapters Universal Deck Adapter Potty Wand

### PERFORMANCE SPECIFICATIONS

Max. Suction Lift (recommended)	20 ft (6 m)	20 ft (6 m)	20 ft (6 m)
Max. Suction Distance (recommended)	100 ft (30 m)	250 ft (75 m)	250 ft (75 m)
Max. Suction Performance*	20 GPM (75 l/min)	50 GPM (190 l/min)	50 GPM (190 l/min)
Max. Discharge Head	30 ft (9 m)	30 ft (9 m)	30 ft (9 m)
Max. Discharge Distance (recommended)	250 ft (75 m)	500 ft (150 m)	500 ft (150 m)
No. of Boats Serviceable at Same Time	1	1	1

### DIMENSIONS

Width	20" (51 cm)	34" (87 cm)	34" (87 cm)
Length	44" (112 cm)	38" (97 cm)	60" (153 cm)
Height	34" (87 cm)	48" (122 cm)	48" (122 cm)
Tank Diameter	14" (36 cm)	30" (76 cm)	30" (76 cm)
Empty Weight	200 lbs (91 kg)	350 lbs (160 kg)	460 lbs (210 kg)
Full Weight	425 lbs (193 kg)	905 lbs (412 kg)	1440 lbs (655 kg)
Intake Port	1 ½"	2"	2"
Discharge Port	1 ½"	2"	2"

\* performance (in US gallons/minute) through full intake port @ 0 ft vertical lift, 1725 rpm

### Standard Features

- Auto cycling between suction and discharge as necessary
- Probe error warning sensor – stops the pump before it gets messy
- Odourless – odour is vented to discharge line
- Easy single switch operation
- Indicator lights to monitor pump mode and tank status
- Pre-wired for standard 120V power outlet (other voltages available)

### Optional Equipment Available

- Remote box or galvanized remote stand for multiple intake locations
- Auto discharge after each use
- Motorized ball valve
- Single hand operated suction nozzle
- Wireless ON-OFF operation
- Token, coin or card reader operation
- Timer controlled pushbutton operation (recommended for self service)
- Hose hangers on tank
- Cycle tank galvanizing and dual coating options available

All WMW control boxes have been UL approved.

Specifications subject to change without notice.



Waubashene, Ontario  
CANADA

**Tel:** 705.538.1495

**Toll Free:** 800.663.1624  
(Canada & US Only)

**Fax:** 705.538.1776

**www.wmwpump.com**